

# Hyosung 6L

**Introduce exceptional bank experiences  
with optimized cash management**

Whether it's optimized cash recycling, a compact design, or our unique secure cash transfer system, the Hyosung 6L lobby ATM brings all the latest advances in banking technology to achieve an elevated in-branch experience.

## Feature Highlights

### Proven Cash Recycling

Reduce operating costs and increase availability

### Small Footprint Design

Seamlessly install in any branch layout or location

### Simplified Engineering

Efficient design ensures superior quality and maintenance

### Selectable Cash Engine Configuration

Choose the cash recycling setup that best meets your needs



15" or 19"  
touchscreen



Recycle up to  
4 denominations



200 notes  
per transaction



Up to 314mm  
capacity per cassette



Selectable cash  
engine configuration

# Specifications

## Dimensions

- Height: 1,425mm (56.1")
- Width: 470mm (18.5")
- Depth: 1,000mm (39.4")
- Weight: 332 kg (732 lbs)

## Environmental Conditions

- Temperature: 0°C ~ 40°C (32°F ~ 104°F)
- Humidity: 25% ~ 85%

## System Platform

- Microsoft Windows® Platform
- Hyosung BlueVerse™ XFS

## Customer Interface

- 15" Touchscreen (19" optional)
- Card reader (Dip or Motorized)
- EMV compliant
- Contactless card reader
- Encrypted pin pad
- Audio jack

## Media Handling

- Bill Recycling Module
- 4 recycling cassettes and 1 deposit cassette
- Recycling cassette: 314mm capacity
- Deposit cassette: 330mm capacity
- Dispense speed: 8 notes/sec
- Automatic shutter
- Bundle up to 200 notes per transaction

## Security

- Safe: UL291 Level-1
- Lock: E-lock + Key lock
- Sensor: Alarm (Heat & Seismic), 3 Door sensors
- Privacy filter viewing angle 60°
- Anti-skimming, Anti-card trapping, Anti-shimming, Anti-cash trapping
- Security camera (Face & Hand)
- BlueVerseSecurity software

## Servicing

- Front Access
- State of health indicators for all modules

## Printer

- Receipt printer: graphical thermal
- E-journal printer or direct thermal line

## Power Supply

- AC 100 ~ 240V ± 10% / Max 8.0A

## Additional Features

- Backup battery (optional)
- Fingerprint scanner (optional)
- Barcode reader (optional)
- Selectable cash engine configuration
- Recycle up to 8 denominations
- Transit Cassette function

Note: Internal components may change with the introduction of new technology. Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.

