

Hyosung 5XL

The very best in cash dispensing technology

The Hyosung 5XL, our second to none cash dispensing ATM, is the perfect solution to ensure cash access - anytime, anywhere. With our proven engineering and designs, the 5XL takes the guess work out of ATM operations to allow for simple and efficient cash withdrawals.



Feature Highlights

Small Footprint Design

Seamlessly install in any branch layout or location

Simplified Engineering

Efficient design ensures superior quality and easier maintenance

Improved Dispensing Technology

Provides more accurate and reliable device cash processing



Compact Footprint



Up to 4 Dispensing
Cassettes



Dispense up to
50 Notes
per Transaction



Up to 334mm
Note Capacity per
Cassette

Specifications

Dimensions

- Height: 1,313 mm (51.7")
- Width: 430 mm (16.9")
- Depth: 728 mm (28.7")
- Weight: 282 kg (621 lbs)

Environmental Conditions

- Temperature: 0°C ~ 40°C (32°F ~ 104°F)
- Humidity 25% ~ 85%

System Platform

- Microsoft Windows® Platform
- Hyosung BlueVerse™ XFS

Customer Interface

- 15" Touchscreen
- 4 x 2 Function keys (optional)
- Card reader (Dip or Motorized)
 - EMV compliant
- Encrypted Pin Pad (PCI compliant)
- Contactless card reader
- Audio jack
- Fingerprint scanner (optional)
- Barcode reader (optional)

Face Camera

Intuitive User Interface

Receipt Printer

Contactless Card Reader

Barcode Reader

Encrypted PIN Pad

Cash Dispenser

Media Handling

- Cash Dispenser
 - Maximum fill level 334mm per cassette
 - Configurable denomination
 - Up to 4 cassettes
 - Reject and retract capability
 - Dispense up to 50 notes per transaction
 - Dispense speed: 5 notes/sec
 - Automatic shutter

Security

- Safe: UL291 Level 1
- Lock: Electronic lock, Mechanical combination lock
- Sensor: Alarm (Heat & Seismic), Door sensors
- Anti-skimming, Anti-shimming, Anti-cash trapping, Anti-card trapping (optional)
- Security camera (Face & Hand)

Servicing

- Front access
- State of health indicators for all modules

Printer

- Receipt printer: graphical thermal
- E-journal printer or direct thermal line

Power Supply

- AC 100 ~ 240V ± 10% / Max 8.0A

Note: Internal components may change with the introduction of new technology. Hyosung TNS reserves the right to change the specifications of this ATM to accommodate the changes in technology.

