

# Hyosung 5XW

**Superior cash dispensing to withstand both attacks and the weather.**

The Hyosung 5XW is a fully weatherized, free-standing cash dispensing ATM that comes with large cassette capacity to ensure customers always have access to their cash. This dispensing ATM is ideal for expanding cash services to new outdoor locations.

## Feature Highlights

### Compact & Robust Design

Easy installation and reliable operation in any outdoor environment

### Simplified Engineering

Efficient design ensures superior quality and easier maintenance

### Improved Dispensing Technology

Provides more accurate and reliable device cash processing

### Weatherized Protection

Robust design and structure protects the ATM from the elements



Compact Footprint



Weatherized  
Design



Up to 4 Dispensing  
Cassettes



Dispense up to  
50 Notes  
per Transaction



Up to 334mm  
Note Capacity per  
Cassette

# Specifications

## Dimensions

- Height: 1,528 mm (60.2")
- Width: 490 mm (19.3")
- Depth: 886 mm (34.9")
- Weight: 570 kg (1,256 lbs)

## Environmental Conditions

- Temperature: -35°C ~ 50°C (-31°F ~ 122°F)
- Humidity: 10% ~ 90%

## System Platform

- Microsoft Windows® Platform
- Hyosung BlueVerse™ XFS

## Customer Interface

- 15" Touchscreen
- Dip type card reader (Motorized optional)
- Contactless card reader
- Barcode reader
- Encrypted pin pad (PCI compliant)
- Audio jack

## Media Handling

- Cash Dispenser
  - Maximum fill level 334mm per cassette
  - Configurable denomination
  - Up to 4 cassettes
  - Reject and retract capability
  - Dispense up to 50 notes per transaction
  - Dispense speed: 5 notes/sec
  - Automatic shutter

## Security

- CEN-III EX-GAS
- Dial lock + Key lock
- Door sensor
- Security face/hand camera

## Servicing

- Front access
- State of health indicators for all modules

## Printer

- 3.1" graphical thermal receipt printer
- E-journal printer or direct thermal line

## Power Supply

- AC 100 ~ 127V ± 10% / 10.0A
- AC 200-240V ± 10% / 6.0A
- Battery backup

## Additional Features

- Lead-through indicator
- Heater (Safe1, Upper2)
- Cooler (Optional)
- Communication – TCP/IP

Note: Internal components may change with the introduction of new technology. Hyosung TNS reserves the right to change the specifications of this device to accommodate the changes in technology.

